

Test Report

(EN 50155 & EN 50121-3-2)

Report No.: CEBDBO-WTW-P22070664-1

Test Model: RCX-2750R-PEG

Series Model: RCX-2XXXXXXXXXXXXXXXXX ("X" can be 0-9, A-Z or blank for marketing purpose)

Received Date: 2022/7/22

Test Date: 2022/8/11 ~ 2022/8/27

Issued Date: 2022/9/21

Applicant: Vecow Co., Ltd.

Address: 3F., No.10, Jiankang Rd., Zhonghe Dist., New Taipei City 23586, Taiwan

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan



This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Table of Contents

| | |
|---|-----------|
| Release Control Record | 4 |
| 1 Certificate of Conformity | 5 |
| 2 Summary of Test Results | 6 |
| 2.1 Performance Criteria | 9 |
| 2.2 Measurement Uncertainty | 9 |
| 2.3 Modification Record..... | 9 |
| 3 General Information | 10 |
| 3.1 Description of EUT | 10 |
| 3.2 Features of EUT | 10 |
| 3.3 Operating Modes of EUT and Determination of Worst Case Operating Mode | 11 |
| 3.4 Test Program Used and Operation Descriptions..... | 11 |
| 3.5 Primary Clock Frequencies of Internal Source | 11 |
| 4 Configuration and Connections with EUT | 12 |
| 4.1 Connection Diagram of EUT and Peripheral Devices..... | 12 |
| 4.2 Configuration of Peripheral Devices and Cable Connections | 14 |
| 5 Conducted Disturbance at Auxiliary a.c. or d.c. Power Ports | 18 |
| 5.1 Limits | 18 |
| 5.2 Test Instruments | 18 |
| 5.3 Test Arrangement | 19 |
| 5.4 Test Results | 20 |
| 6 Radiated Disturbance up to 1 GHz | 22 |
| 6.1 Limits | 22 |
| 6.2 Test Instruments | 22 |
| 6.3 Test Arrangement | 23 |
| 6.4 Test Results | 24 |
| 7 Radiated Disturbance above 1 GHz | 26 |
| 7.1 Limits | 26 |
| 7.2 Test Instruments | 27 |
| 7.3 Test Arrangement | 28 |
| 7.4 Test Results | 29 |
| 8 Harmonics Current Measurement | 31 |
| 8.1 Limits | 31 |
| 8.2 Classification of Equipment..... | 31 |
| 8.3 Test Instruments | 31 |
| 8.4 Test Arrangement | 32 |
| 8.5 Test Results | 33 |
| 9 Voltage Fluctuations and Flicker Measurement | 34 |
| 9.1 Limits | 34 |
| 9.2 Test Instruments | 34 |
| 9.3 Test Arrangement | 34 |
| 9.4 Test Results | 35 |
| 10 Electrostatic Discharge Immunity Test (ESD) | 36 |
| 10.1 Test Specification..... | 36 |
| 10.2 Test Instruments | 36 |
| 10.3 Test Arrangement | 37 |
| 10.4 Test Results | 38 |

| | | |
|---|---|-----------|
| 11 | Radio-frequency Electromagnetic Field Immunity Test (RS) | 43 |
| 11.1 | Test Specification..... | 43 |
| 11.2 | Test Instruments | 44 |
| 11.3 | Test Arrangement | 45 |
| 11.4 | Test Results | 45 |
| 12 | Electrical Fast Transient/Burst Immunity Test (EFT) | 46 |
| 12.1 | Test Specification..... | 46 |
| 12.2 | Test Instruments | 46 |
| 12.3 | Test Arrangement | 47 |
| 12.4 | Test Results | 48 |
| 13 | Surge Immunity Test | 49 |
| 13.1 | Test Specification..... | 49 |
| 13.2 | Test Instruments | 49 |
| 13.3 | Test Arrangement | 50 |
| 13.4 | Test Results | 50 |
| 14 | Immunity to Conducted Disturbances Induced by RF Fields (CS) | 51 |
| 14.1 | Test Specification..... | 51 |
| 14.2 | Test Instruments | 51 |
| 14.3 | Test Arrangement | 53 |
| 14.4 | Test Results | 54 |
| 15 | Pictures of Test Arrangements | 55 |
| 15.1 | Conducted Disturbance at Auxiliary a.c. or d.c. power ports | 55 |
| 15.2 | Radiated Disturbance up to 1 GHz | 56 |
| 15.3 | Radiated Disturbance above 1 GHz..... | 57 |
| 15.4 | Harmonics Current, Voltage Fluctuations and Flicker Measurement..... | 58 |
| 15.5 | Electrostatic Discharge Immunity Test (ESD) | 58 |
| 15.6 | Radio-frequency Electromagnetic Field Immunity Test (RS) | 59 |
| 15.7 | Fast Transients (EFT)..... | 60 |
| 15.8 | Surge | 62 |
| 15.9 | Radio-frequency common mode (CS)..... | 63 |
| Appendix – Information of the Testing Laboratories | | 65 |

Release Control Record


| Issue No. | Description | Date Issued |
|------------------------|-------------------|-------------|
| CEBDBO-WTW-P22070664-1 | Original release. | 2022/9/21 |

1 Certificate of Conformity

Product: AI Computing System
Brand: Vecow
Test Model: RCX-2750R-PEG
Series Model: RCX-2XXXXXXXXXXXXXXXXX ("X" can be 0-9, A-Z or blank for marketing purpose)
Sample Status: Engineering sample
Applicant: Vecow Co., Ltd.
Test Date: 2022/8/11 ~ 2022/8/27
Standards: EN 50155:2017, Clause 13.4.8
EN 61000-3-2:2014, Class D
EN IEC 61000-3-2:2019 +A1:2021, Class D
EN 61000-3-3:2013 +A2:2021
EN 50121-1:2017
EN 50121-3-2:2016
EN 61000-4-2:2009
EN 61000-4-3:2006 +A1:2008 +A2:2010
EN IEC 61000-4-3:2020
EN 61000-4-4:2012
EN 61000-4-5:2014 +A1:2017
EN 61000-4-6:2014 +AC:2015

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :  , Date: 2022/9/21
Vivian Chen / Senior Specialist

Approved by :  , Date: 2022/9/21
Jim Hsiang / Associate Technical Manager

2 Summary of Test Results

| EN 50121-3-2:2016, Emission requirements, EN 50155:2017, Clause 13.4.8 | | | |
|---|---|---|---------|
| Port | Test Item / specifications | Result/Remarks | Verdict |
| Auxiliary a.c. or d.c. power ports - Auxiliary supply sinusoidal a.c. or d.c. | Conducted disturbance 150 kHz- 500 kHz: 99 dB μ V quasi-peak 500 kHz- 30 MHz: 93 dB μ V quasi-peak | Minimum passing margin is -56.80 dB at 12.57561 MHz | Pass |
| Auxiliary a.c. or d.c. power ports – AC power outlet port for public use | Conducted disturbance 50 Hz- 2 kHz: THD <8% (THD: total harmonic distortion) | Test not applicable because the port does not exist. | N/A |
| Battery referenced ports - Battery power supply | Conducted disturbance 150 kHz- 500 kHz: 99 dB μ V quasi-peak 500 kHz- 30 MHz: 93 dB μ V quasi-peak | Test not applicable because the port does not exist. | N/A |
| Enclosure | Radiated disturbance 30 MHz- 230 MHz: 40 dB μ V/m quasi-peak 230 MHz -1 GHz: 47 dB μ V/m quasi-peak | Minimum passing margin is -5.78 dB at 216.03 MHz | Pass |
| Enclosure | Radiated disturbance 1 GHz- 3 GHz: 76 dB μ V/m peak 56 dB μ V/m average 3 GHz - 6 GHz: 80 dB μ V/m peak 60 dB μ V/m average | Minimum passing margin is -6.88 dB at 5400.03 MHz | Pass |

| Emission requirements | | | |
|--|----------------------------------|---|---------|
| Standard | Test Item / specifications | Result/Remarks | Verdict |
| EN 61000-3-2:2014 EN IEC 61000-3-2:2019+A1:2021 | Harmonic current emissions | Class D | Pass |
| EN 61000-3-3:2013+A2:2021 | Voltage fluctuations and flicker | $P_{st} \leq 1.0$ $d_{max} \leq 4\%$ $P_{it} \leq 0.65$ $d_c \leq 3.3\%$ $T_{max} \leq 500ms$ | Pass |

EN 50121-3-2:2016, Immunity requirements,
EN 50155:2017, Clause 13.4.8

| Table Clause | Basic standard | Port | Test Item / specifications | Result/Remarks | Verdict |
|--------------|--|---|--|-------------------------|---------|
| 3.1 | EN 61000-4-6:2014 +AC:2015 | Battery referenced ports (except at the output of energy sources), Auxiliary a.c. power input ports (rated voltage ≤ 400 Vrms) | Radio-frequency common mode (CS) 80% AM (1kHz) 0.15-80 MHz, 10V Performance Criterion A | Performance Criterion A | Pass |
| 3.2 | EN 61000-4-4:2012 | Battery referenced ports (except at the output of energy sources), Auxiliary a.c. power input ports (rated voltage ≤ 400 Vrms) | Fast Transients (EFT) 5/50 (tr/tw) ns, 5kHz ± 2 kV Performance Criterion A | Performance Criterion A | Pass |
| 3.3 | EN 61000-4-5:2014 +A1:2017 | Battery referenced ports (except at the output of energy sources), Auxiliary a.c. power input ports (rated voltage ≤ 400 Vrms) | Surges 1.2/50 (8/20) (T _i /T _d) μ s Line to ground: ± 2 kV 42 Ω , 0.5 μ F Line to line: ± 1 kV 42 Ω , 0.5 μ F Performance Criterion B | Performance Criterion A | Pass |
| 4.1 | EN 61000-4-6:2014 +AC:2015 | Signal & communication, process measurement & control ports | Radio-frequency common mode (CS) 80% AM (1kHz) 0.15-80 MHz, 10V Performance Criterion A | Performance Criterion A | Pass |
| 4.2 | EN 61000-4-4:2012 | Signal & communication, process measurement & control ports | Fast Transients (EFT) 5/50 (tr/tw) ns, 5kHz ± 2 kV, Capacitive clamp Performance Criterion A | Performance Criterion A | Pass |
| 5.1 | EN 61000-4-3:2006 +A1:2008 +A2:2010/ EN IEC 61000-4-3:2020 | Enclosure ports | Radio-frequency electromagnetic field amplitude modulated (RS) ¹ , 80% AM (1kHz) 80-800 MHz, 20V/m Performance Criterion A | Performance Criterion A | Pass |
| 5.2 | EN 61000-4-3:2006 +A1:2008 +A2:2010/ EN IEC 61000-4-3:2020 | Enclosure ports | Radio-frequency electromagnetic field from digital mobile telephones (RS) ² , 80% AM (1kHz) 800-1000 MHz, 20V/m 1400-2000 MHz, 10V/m 2000-2700 MHz, 5V/m 5100-6000 MHz, 3V/m Performance Criterion A | Performance Criterion A | Pass |

EN 50121-3-2:2016, Immunity requirements,
EN 50155:2017, Clause 13.4.8

| Table Clause | Basic standard | Port | Test Item / specifications | Result/Remarks | Verdict |
|--------------|-------------------|-----------------|---|-------------------------|---------|
| 5.3 | EN 61000-4-2:2009 | Enclosure ports | Electrostatic Discharges (ESD) ±6kV Contact discharge ±8kV Air discharge Performance Criterion B | Performance Criterion B | Pass |

Note 1: This limit applies to equipment mounted in the passenger compartments, drivers cab or external to the rolling stock (roof, underframe). For equipment mounted in all other areas a severity level of 10 V/m may be used.

Note 2: For large apparatus (e.g. traction drives, auxiliary converters) it is often not practical to perform the immunity test to radiated electromagnetic fields on the complete unit. In such cases the manufacturer should test susceptible sub-systems (e.g. control electronics). The test report should justify the selection or not of sub-systems and any assumptions made (e.g. reduction of field due to case shielding).

Note:

1. There is no deviation to the applied test methods and requirements covered by the scope of this report.
2. The above EN basic standards are applied with latest version if customer has no special requirement.
3. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.
4. N/A: Not Applicable

2.1 Performance Criteria

General Performance Criteria

The general performance criteria apply for those ports for which no specific performance criteria are defined (e.g. auxiliary ports) in the report.

Performance criterion A: The apparatus shall continue to operate as intended during and after the test. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. The performance level may be replaced by a permissible loss of performance. If the minimum performance level or the permissible performance loss is not specified by the manufacturer, either of these may be derived from the product description and documentation, and from what the user may reasonably expect from the apparatus if used as intended..

Performance criterion B: The apparatus shall continue to operate as intended after the test. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. The performance level may be replaced by a permissible loss of performance. During the test, degradation of performance is however allowed. No change of actual operating state or stored data is allowed. If the minimum performance level or the permissible performance loss is not specified by the manufacturer, either of these may be derived from the product description and documentation, and from what the user may reasonably expect from the apparatus if used as intended.

Performance criterion C: Temporary loss of function is allowed, provided the function is self-recoverable or can be restored by the operation of the controls.

2.2 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

| Measurement | Expanded Uncertainty (k=2) (\pm) | Maximum allowable uncertainty (\pm) |
|--|---|--|
| Conducted disturbance at mains port using AMN, 150kHz ~ 30MHz | 3.00 dB | 3.4 dB (U_{CISPR}) |
| Radiated disturbance, 30MHz ~ 1GHz | 4.30 dB | 6.3 dB (U_{CISPR}) |
| Radiated disturbance, 1GHz ~ 6GHz | 4.64 dB | 5.2 dB (U_{CISPR}) |

The other instruments specified are routine verified to remain within the calibrated levels, no measurement uncertainty is required to be calculated.

2.3 Modification Record

There were no modifications required for compliance.

3 General Information

3.1 Description of EUT

| | |
|---------------------|---|
| Product | AI Computing System |
| Brand | Vecow |
| Test Model | RCX-2750R-PEG |
| Series Model | RCX-2XXXXXXXXXXXXXXXXX ("X" can be 0-9, A-Z or blank for marketing purpose) |
| Model Difference | For marketing purpose. |
| Sample Status | Engineering sample |
| Operating Software | WIN 10 PRO, Burnintest V9.2 |
| Power Supply Rating | DC from Adapter |
| Accessory Device | N/A |
| Data Cable Supplied | N/A |

Note:

The EUT uses following adapter.

| | |
|--------------|--|
| Brand | LITEON |
| Model | PA-1331-92E |
| Input Power | 100-240V, 50-60Hz, 4.4A |
| Output Power | +24V, 13.75A, 330W |
| Power Line | AC (3-Pin) cable (1.8m) DC cable (1.0m) with two ferrite cores. |

3.2 Features of EUT

1. The tests reported herein were performed according to the method specified by Vecow Co., Ltd., for detailed feature description, please refer to the manufacturer's specifications or user's manual.

1. The EUT configured with the following key components:

| Components | Brand | Model | Specification |
|------------|----------|-----------------------|---------------------------------|
| CPU | Intel | i7-11700 | Intel® Core™ i7-11700 Processor |
| RAM | INNODISK | M4S0-AGS 1O5IK-H03 | 16GB DDR4 2666 W/T SODIMM |
| DRAM | VECOW | VMD4NIT-08G00A | 8GB DDR4-2666-19 SODIMM WT |
| SSD | INNODISK | DES25-A28M41BW1DC-H03 | 128GB 2.5" SATA SSD 3ME4 |

3.3 Operating Modes of EUT and Determination of Worst Case Operating Mode

1. The EUT is designed with AC power of rating 100-240Vac, 50-60Hz. For radiated emission evaluation, 230Vac/50Hz (for EN 50155), 120Vac/60Hz (for FCC Part 15) had been covered during the pre-test. The worst data was found at **230Vac/50Hz** and recorded in the applied test report.
2. Test modes are presented in the report as below.

| Mode | Test Condition | Input Power |
|------|----------------|--------------|
| A | Full System | 230Vac/ 50Hz |

3.4 Test Program Used and Operation Descriptions

Emission tests (Harmonics & Flicker excluded):

- a. Turned on the power of all equipments.
- b. EUT ran a test program to enable all functions.
- c. EUT read and wrote messages to/ from SSD, and ext. HDDs.
- d. IP camera captured video / audio signal to EUT.
- e. EUT sent and received ping messages to/ from the Notebook PCs (kept in a remote area) via two STP LAN cables (10m each).
- f. EUT sent "H" messages to ext. LCD monitors. Then they displayed "H" messages on their screens simultaneously.
- g. EUT sent "1kHz audio" signal to earphone.
- h. EUT sent messages to printer and printed them out.
- i. Steps c-h were repeated.

Harmonics & Flicker & Immunity tests:

- a. Turned on the power of all equipments.
- b. EUT ran a test program to enable all functions.
- c. EUT read and wrote messages to/ from SSD, and USB Flash.
- d. IP camera captured video / audio signal to EUT.
- e. EUT sent and received ping messages to/ from the Notebook PCs (kept in a remote area) via two STP LAN cables (10m each).
- f. EUT sent "color bars with moving element" messages to ext. LCD monitors. Then they displayed "color bars with moving element" messages on their screens simultaneously.
- g. EUT sent audio signal to speaker.
- h. Steps c-g were repeated.


3.5 Primary Clock Frequencies of Internal Source

The highest frequency generated or used within the EUT or on which the EUT operates or tunes is 2.5GHz, provided by Vecow Co., Ltd., for detailed internal source, please refer to the manufacturer's specifications.


4 Configuration and Connections with EUT

4.1 Connection Diagram of EUT and Peripheral Devices

Emission tests (Harmonics & Flicker excluded):



Harmonics & Flicker & Immunity tests:



4.2 Configuration of Peripheral Devices and Cable Connections

Emission tests (Harmonics & Flicker excluded):

| ID | Product | Brand | Model No. | Serial No. | FCC ID | Remarks |
|----|---------------------------------------|---------|---------------------------|------------------------------|------------------|-----------------------|
| A | Monitor | ASUS | VG289Q | M1LMTF385740 | NA | M1-010634 |
| B | Monitor | ASUS | VG289Q | M1LMTF385742 | NA | M1-010635 |
| C | Monitor | ASUS | VG289Q | M1LMTF385832 | NA | M1-010637 |
| D | USB 3.1 SSD | Crucial | CT500X8SSD9 | 1941E320114D | NA | H4-010856 |
| E | USB 3.1 SSD | Crucial | CT500X8SSD9 | 1943E3201B6D | NA | H4-010859 |
| F | USB 3.1 SSD | Crucial | CT500X8SSD9 | 1940E3200CFB | NA | H4-010849 |
| G | USB Mouse | DELL | MOCZUL | CN-049TWY-PR C00-77B-007E | NA | M4-010884 |
| H | USB Keyboard | Dell | KB216t | CN-0W33XP-LO 300-7CL-1909 | NA | K1-010798 |
| I | EARPHONE | PHILIPS | SBC HL145 | N/A | NA | H2-010180 |
| J | Microphone | E-books | E-EPB099 | N/A | NA | M5-010144 |
| K | IP CAMARA | 3MP | MBL030A-ORZ0310 | NA | DOC | Supplied by applicant |
| L | IP CAMARA | 3MP | MBL030A-ORZ0310 | NA | DOC | Supplied by applicant |
| M | IP CAMARA | 3MP | MBL030A-ORZ0310 | NA | DOC | Supplied by applicant |
| N | IP CAMARA | 3MP | MBL030A-ORZ0310 | NA | DOC | Supplied by applicant |
| O | Printer | HP | HP Officejet Pro 251dW | NA | B94SDGOB11 91 | Provided by Lab |
| P | RS232 Terminal | N/A | NA | N/A | NA | Supplied by applicant |
| Q | ADAPTER | LITEON | PA-1331-92E | N/A | NA | Supplied by applicant |
| R | Laptop | LENOVO | T480 | PF1EZSAW | NA | N1-010484 |
| S | 10G LAN card | ASUS | XG-C100C | NA | DoC | Provided by Lab |
| T | PC | DELL | 3010 SF | 1JWQS02 | NA | Provided by Lab |
| U | RS232 Terminal | N/A | NA | N/A | NA | Supplied by applicant |
| V | RS232 Terminal | N/A | NA | N/A | NA | Supplied by applicant |
| W | RS232 Terminal | N/A | NA | N/A | NA | Supplied by applicant |
| X | PCI Express PoE+ Expansion Card | Vecow | PE-2004MX | NA | NA | Supplied by applicant |

| ID | Cable Descriptions | Qty. | Length (m) | Shielding (Yes/No) | Cores (Qty.) | Remarks |
|----|-----------------------|------|------------|--------------------|--------------|-----------------------|
| 1 | DP cable | 3 | 1.8 | Yes | 0 | Provided by Lab |
| 2 | USB Type A to C cable | 3 | 1 | Yes | 0 | Provided by Lab |
| 3 | USB 2.0 cable | 1 | 1.8 | Yes | 0 | Provided by Lab |
| 4 | USB 2.0 cable | 1 | 1.8 | Yes | 0 | Provided by Lab |
| 5 | Audio (3.5") cable | 1 | 1.2 | No | 0 | Provided by Lab |
| 6 | Audio (3.5") cable | 1 | 2 | No | 0 | Provided by Lab |
| 7 | DIO cable | 2 | 1 | No | 0 | Provided by Lab |
| 8 | RJ45 (Cat. 5e) cable | 2 | 2 | Yes | 0 | Supplied by applicant |
| 9 | USB cable | 1 | 1.5 | Yes | 0 | Provided by Lab |
| 10 | GND (PE) cable | 1 | 1.5 | No | 0 | Provided by Lab |
| 11 | DC power cable | 1 | 1 | No | 2 | Supplied by applicant |
| 12 | AC power cable | 1 | 1.8 | No | 0 | Accessory of EUT |
| 13 | RJ45 (Cat. 5e) cable | 1 | 10 | Yes | 0 | Provided by Lab |
| 14 | RJ45 (Cat. 5e) cable | 1 | 10 | Yes | 0 | Provided by Lab |
| 15 | RJ45 (Cat. 5e) cable | 2 | 1 | Yes | 0 | Supplied by applicant |
| 16 | RJ45 (Cat. 5e) cable | 2 | 0.1 | Yes | 0 | Supplied by applicant |
| 17 | RJ45 (Cat. 5e) cable | 2 | 0.1 | Yes | 0 | Supplied by applicant |

Harmonics, Flicker, Immunity tests:

| ID | Product | Brand | Model No. | Serial No. | FCC ID | Remarks |
|----|---------------------------------|-----------|---------------------|--------------------------|--------|-----------------------|
| A | Monitor | Vita | VT-270JTG2 | 204270JTFE001 | DoC | Provided by Lab |
| B | Monitor | DELL | P2415Qb | CN-OGTTPW-74261-662-OAGL | N/A | Provided by Lab |
| C | Monitor | DELL | P2415Qb | CN-OGTTPW-74261-662-OAAL | N/A | Provided by Lab |
| D | USB K/B | Microsoft | 1576 | N/A | N/A | Provided by Lab |
| E | USB M/S | Microsoft | MSK-1113(B) | N/A | N/A | Provided by Lab |
| F | USB 3.0 Dongle | HP | x750w | N/A | N/A | Provided by Lab |
| G | USB 3.0 Dongle | HP | x750w | N/A | N/A | Provided by Lab |
| H | USB 3.0 Dongle | HP | x750w | N/A | N/A | Provided by Lab |
| I | USB 3.0 Dongle | HP | x750w | N/A | N/A | Provided by Lab |
| J | Speaker | N/A | N/A | N/A | N/A | Provided by Lab |
| K | Microphone | V-COOL | M2/MIC01 | N/A | N/A | Provided by Lab |
| L | RS232 Terminal | N/A | N/A | N/A | N/A | Supplied by applicant |
| M | RS232 Terminal | N/A | N/A | N/A | N/A | Supplied by applicant |
| N | RS232 Terminal | N/A | N/A | N/A | N/A | Supplied by applicant |
| O | RS232 Terminal | N/A | N/A | N/A | N/A | Supplied by applicant |
| P | POE IP CAMARA | 3MP | MBL030A-ORZ0310 | N/A | DOC | Supplied by applicant |
| Q | POE IP CAMARA | 3MP | MBL030A-ORZ0310 | N/A | DOC | Supplied by applicant |
| R | POE IP CAMARA | 3MP | MBL030A-ORZ0310 | N/A | DOC | Supplied by applicant |
| S | POE IP CAMARA | 3MP | MBL030A-ORZ0310 | N/A | DOC | Supplied by applicant |
| T | Laptop | DELL | P41G | FT4W952 | N/A | Provided by Lab |
| U | PC | DELL | OptiPlex 390SF Base | F3PVWBX | N/A | Provided by Lab |
| V | 10G LAN card | ASUS | XG-C100C | N/A | DoC | Provided by Lab |
| W | PCI Express PoE+ Expansion Card | Vecow | PE-2004MX | NA | NA | Supplied by applicant |

| ID | Cable Descriptions | Qty. | Length (m) | Shielding (Yes/No) | Cores (Qty.) | Remarks |
|----|-----------------------------|------|------------|--------------------|--------------|-----------------------|
| 1 | DP cable | 3 | 1.8 | Yes | 0 | Provided by Lab |
| 2 | USB 2.0 cable | 1 | 2 | Yes | 0 | Provided by Lab |
| 3 | USB 2.0 cable | 1 | 1.8 | Yes | 0 | Provided by Lab |
| 4 | Audio (3.5") cable | 1 | 1.2 | No | 0 | Provided by Lab |
| 5 | Audio (3.5") cable | 1 | 1.5 | No | 0 | Provided by Lab |
| 6 | Data cable | 1 | 0.55 | No | 0 | Supplied by applicant |
| 7 | Shield RJ45 (Cat. 5e) cable | 3 | 0.3 | Yes | 0 | Supplied by applicant |
| 8 | GND | 1 | 3 | No | 0 | Provided by Lab |
| 9 | DC power cable | 1 | 1 | No | 2 | Accessory of EUT |
| 10 | AC power(3pin) cable | 1 | 1.8 | No | 0 | Accessory of EUT |
| 11 | Shield RJ45 (Cat. 5e) cable | 1 | 10 | Yes | 0 | Provided by Lab |
| 12 | Shield RJ45 (Cat. 5e) cable | 1 | 10 | Yes | 0 | Provided by Lab |
| 13 | Data cable | 2 | 0.9 | No | 0 | Supplied by applicant |
| 14 | Shield RJ45 (Cat. 5e) cable | 1 | 0.3 | Yes | 0 | Supplied by applicant |
| 15 | Shield RJ45 (Cat. 5e) cable | 1 | 2 | Yes | 0 | Supplied by applicant |
| 16 | Shield RJ45 (Cat. 5e) cable | 1 | 1 | Yes | 0 | Supplied by applicant |

5 Conducted Disturbance at Auxiliary a.c. or d.c. Power Ports

5.1 Limits

| Frequency (MHz) | Quasi-peak, (dBuV) |
|-----------------|--------------------|
| 0.15 - 0.5 | 99 |
| 0.5 - 30 | 93 |

Notes: 1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases linearly with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

5.2 Test Instruments

| Description Manufacturer | Model No. | Serial No. | Calibrated Date | Calibrated Until |
|---|---------------|--------------|--------------------|---------------------|
| 50 ohm terminal LYNICS | 0900510 | E1-011285 | 2021/10/1 | 2022/9/30 |
| | | E1-011286 | 2021/10/1 | 2022/9/30 |
| 50 Ohms Terminator LYNICS | 0900510 | E1-01-305 | 2022/2/9 | 2023/2/8 |
| Attenuator STI | STI02-2200-10 | NO.3 | 2021/10/22 | 2022/10/21 |
| Coupling/Dcoupling Network Schwarzbeck | CDNE-M2 | 00097 | 2022/6/1 | 2023/5/31 |
| | | 00091 | 2022/6/1 | 2023/5/31 |
| Coupling/Dcoupling Network TESEQ | CDN A201A | 44601 | 2021/12/22 | 2022/12/21 |
| DC LISN R&S | ESH3-Z6 | 100219 | 2022/8/2 | 2023/8/1 |
| | | 844950/018 | 2022/8/2 | 2023/8/1 |
| DC LISN Schwarzbeck | NNLK 8121 | 8121-808 | 2022/4/29 | 2023/4/28 |
| Isolation Transformer Erika Fiedler | D-65396 | 017 | 2021/9/9 | 2022/9/8 |
| LISN EMCO | 3825/2 | 9204-1964 | 2022/6/17 | 2023/6/16 |
| | | 9504-2359 | 2022/8/2 | 2023/8/1 |
| LISN R&S | ENV216 | 101195 | 2022/8/1 | 2023/7/31 |
| | | 101196 | 2022/5/24 | 2023/5/23 |
| | | 101197 | 2022/7/5 | 2023/7/4 |
| LISN Schwarzbeck | NNLK 8121 | 8121-731 | 2022/5/26 | 2023/5/25 |
| | | 8121-00759 | 2021/8/17 | 2022/8/16 |
| | NNLK8129 | 8129229 | 2022/6/8 | 2023/6/7 |
| Receiver R&S | ESCI | 100412 | 2021/8/26 | 2022/8/25 |
| RF Coaxial Cable Commate | 5D-FB | Cable-CO3-01 | 2021/9/15 | 2022/9/14 |
| Software BVADT | Cond_V7.3.7.4 | N/A | N/A | N/A |


Notes:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in Linkou Conduction 3.
3. Tested Date: 2022/8/11

5.3 Test Arrangement

- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The test results of conducted emissions at mains ports are recorded of six worst margins for quasi-peak (mandatory) [and average (if necessary)] values against the limits at frequencies of interest unless the margin is 20 dB or greater.

Note: The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.



Note: Support units were connected to second LISN.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

5.4 Test Results


Mode A

| | | | |
|------------------------|------------------|---|-----------------------|
| Frequency Range | 150 kHz ~ 30 MHz | Detector Function & Resolution Bandwidth | Quasi-Peak (QP), 9kHz |
| Input Power | 230 Vac, 50 Hz | Environmental Conditions | 26°C, 70% RH |
| Tested by | Ed. Lin | | |

| Phase Of Power : Line (L) | | | | | | |
|---------------------------|-----------------|------------------------|----------------------|-----------------------|--------------|-------------|
| No | Frequency (MHz) | Correction Factor (dB) | Reading Value (dBuV) | Emission Level (dBuV) | Limit (dBuV) | Margin (dB) |
| | | | Q.P. | Q.P. | Q.P. | Q.P. |
| 1 | 0.23604 | 9.65 | 31.47 | 41.12 | 99.00 | -57.88 |
| 2 | 0.37293 | 9.67 | 28.49 | 38.16 | 99.00 | -60.84 |
| 3 | 2.39110 | 9.75 | 25.41 | 35.16 | 93.00 | -57.84 |
| 4 | 4.66730 | 9.80 | 24.30 | 34.10 | 93.00 | -58.90 |
| 5 | 6.38840 | 9.83 | 22.78 | 32.61 | 93.00 | -60.39 |
| 6 | 12.57561 | 9.90 | 26.28 | 36.18 | 93.00 | -56.82 |

Remarks:

1. Q.P. is abbreviations of quasi-peak individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




| | | | |
|------------------------|------------------|---|-----------------------|
| Frequency Range | 150 kHz ~ 30 MHz | Detector Function & Resolution Bandwidth | Quasi-Peak (QP), 9kHz |
| Input Power | 230 Vac, 50 Hz | Environmental Conditions | 26°C, 70% RH |
| Tested by | Ed. Lin | | |

| Phase Of Power : Neutral (N) | | | | | | |
|------------------------------|-----------------|------------------------|----------------------|-----------------------|--------------|---------------|
| No | Frequency (MHz) | Correction Factor (dB) | Reading Value (dBuV) | Emission Level (dBuV) | Limit (dBuV) | Margin (dB) |
| | | | Q.P. | Q.P. | Q.P. | Q.P. |
| 1 | 0.23586 | 9.65 | 29.62 | 39.27 | 99.00 | -59.73 |
| 2 | 2.39501 | 9.76 | 21.93 | 31.69 | 93.00 | -61.31 |
| 3 | 3.59178 | 9.79 | 21.76 | 31.55 | 93.00 | -61.45 |
| 4 | 4.64775 | 9.81 | 24.99 | 34.80 | 93.00 | -58.20 |
| 5 | 6.13419 | 9.84 | 22.87 | 32.71 | 93.00 | -60.29 |
| 6 | 12.57561 | 9.96 | 26.24 | 36.20 | 93.00 | -56.80 |

Remarks:

1. Q.P. is abbreviations of quasi-peak individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



6 Radiated Disturbance up to 1 GHz

6.1 Limits

| Frequency (MHz) | dBuV/m (at 10m) / quasi-peak |
|-----------------|------------------------------|
| 30 - 230 | 40 |
| 230 - 1000 | 47 |

- Notes:
1. The lower limit shall apply at the transition frequencies.
 2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

6.2 Test Instruments

| Description Manufacturer | Model No. | Serial No. | Calibrated Date | Calibrated Until |
|---|----------------------|--------------|--------------------|---------------------|
| ADT. Tower | AT100 | 0205 | N/A | N/A |
| ADT. Turn Table | TT100 | 0205 | N/A | N/A |
| Attenuator Mini-Circuits | UNAT-5+ | PAD-ST2-01 | 2021/10/22 | 2022/10/21 |
| Bi-log Broadband Antenna Schwarzbeck | VULB9168 | 9168-303 | 2021/10/29 | 2022/10/28 |
| Coupling/Dcoupling Network Schwarzbeck | CDNE-M2 | 00097 | 2022/6/1 | 2023/5/31 |
| | CDNE-M3 | 00091 | 2022/6/1 | 2023/5/31 |
| Preamplifier Agilent | 8447D | 2944A11062 | 2022/2/16 | 2023/2/15 |
| Pre_Amplifier EMCI | EMC9135 | 980711 | 2022/3/19 | 2023/3/18 |
| Pre_Amplifier HP | 8447D | 2944A08313 | 2022/2/16 | 2023/2/15 |
| RF Coaxial Cable Pacific | 8D-FB | Cable-ST2-01 | 2021/10/22 | 2022/10/21 |
| Software BVADT | Radiated_V7.6.15.9.5 | N/A | N/A | N/A |
| TEST RECEIVER R&S | ESCS 30 | 100276 | 2022/4/19 | 2023/4/18 |
| | | 100292 | 2021/9/1 | 2022/8/31 |


Notes:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in Linkou Open Site2 , The test site validated date: 2022/7/16 (NSA)
3. Tested Date: 2022/8/12

6.3 Test Arrangement

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at an accredited test facility. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is up to 1 GHz.

Note: The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for quasi-peak detection (QP) at frequency up to 1GHz.



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

6.4 Test Results

Mode A


| | | | |
|------------------------|----------------|---|--------------------------|
| Frequency Range | 30 MHz ~ 1 GHz | Detector Function & Resolution Bandwidth | Quasi-Peak (QP), 120 kHz |
| Input Power | 230 Vac, 50 Hz | Environmental Conditions | 33°C, 69% RH |
| Tested By | Paul Chen | | |

Antenna Polarity & Test Distance : Horizontal at 10 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|----|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| 1 | 51.17 | 28.37 QP | 40.00 | -11.63 | 4.00 H | 150 | 37.10 | -8.73 |
| 2 | 124.93 | 29.64 QP | 40.00 | -10.36 | 4.00 H | 304 | 39.35 | -9.71 |
| 3 | 216.03 | 33.36 QP | 40.00 | -6.64 | 4.00 H | 189 | 43.58 | -10.22 |
| 4 | 324.15 | 40.77 QP | 47.00 | -6.23 | 3.27 H | 228 | 46.11 | -5.34 |
| 5 | 450.00 | 36.19 QP | 47.00 | -10.81 | 2.16 H | 78 | 38.99 | -2.80 |
| 6 | 500.00 | 37.71 QP | 47.00 | -9.29 | 1.87 H | 108 | 39.51 | -1.80 |
| 7 | 550.14 | 38.71 QP | 47.00 | -8.29 | 1.75 H | 260 | 39.42 | -0.71 |
| 8 | 662.48 | 38.21 QP | 47.00 | -8.79 | 1.31 H | 139 | 36.17 | 2.04 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
– Pre-Amplifier Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value




| | | | |
|------------------------|----------------|---|--------------------------|
| Frequency Range | 30 MHz ~ 1 GHz | Detector Function & Resolution Bandwidth | Quasi-Peak (QP), 120 kHz |
| Input Power | 230 Vac, 50 Hz | Environmental Conditions | 33°C, 69% RH |
| Tested By | Paul Chen | | |

| Antenna Polarity & Test Distance : Vertical at 10 m | | | | | | | | |
|---|-----------------|-------------------------|----------------|--------------|--------------------|----------------------|------------------|--------------------------|
| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1 | 33.48 | 28.85 QP | 40.00 | -11.15 | 1.23 V | 100 | 38.97 | -10.12 |
| 2 | 71.76 | 28.05 QP | 40.00 | -11.95 | 1.78 V | 166 | 39.46 | -11.41 |
| 3 | 125.01 | 33.65 QP | 40.00 | -6.35 | 1.00 V | 114 | 43.33 | -9.68 |
| 4 | 165.04 | 31.39 QP | 40.00 | -8.61 | 1.00 V | 277 | 39.14 | -7.75 |
| 5 | 216.03 | 34.22 QP | 40.00 | -5.78 | 1.00 V | 113 | 44.44 | -10.22 |
| 6 | 297.00 | 35.98 QP | 47.00 | -11.02 | 1.00 V | 201 | 42.17 | -6.19 |
| 7 | 324.15 | 37.02 QP | 47.00 | -9.98 | 1.00 V | 194 | 42.36 | -5.34 |
| 8 | 500.02 | 33.05 QP | 47.00 | -13.95 | 1.00 V | 304 | 34.85 | -1.80 |
| 9 | 662.48 | 33.92 QP | 47.00 | -13.08 | 3.27 V | 292 | 31.88 | 2.04 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Pre-Amplifier Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value



7 Radiated Disturbance above 1 GHz

7.1 Limits

| Frequency (GHz) | dBuV/m (at 3m) | |
|-----------------|----------------|------|
| | Average | Peak |
| 1 to 3 | 56 | 76 |
| 3 to 6 | 60 | 80 |

- Notes:
1. The lower limit shall apply at the transition frequencies.
 2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

Frequency Range (For unintentional radiators)

| Highest frequency generated or used in the EUT or on which the EUT operates or tunes (MHz) | Upper frequency of measurement range (MHz) |
|--|--|
| Below 108 | 1000 |
| 108-500 | 2000 |
| 500-1000 | 5000 |
| Above 1000 | Up to 5 times of the highest frequency or 6 GHz, whichever is less |

7.2 Test Instruments

| Description Manufacturer | Model No. | Serial No. | Calibrated Date | Calibrated Until |
|---|-------------------|----------------------|--------------------|---------------------|
| Attenuator Mini-Circuits | BW-K3-2W44+ | PAD-CH7-03 | 2022/7/7 | 2023/7/6 |
| | BW-N4W5+ | PAD-CH10-02 | 2022/7/7 | 2023/7/6 |
| Band Pass Filter MICRO-TRONICS | BRM17690 | 005 | 2022/5/26 | 2023/5/25 |
| Fix tool for Boresight antenna tower BV | BAF-01 | 9 | N/A | N/A |
| Horn Antenna EMCO | 3115 | 6714 | 2021/11/14 | 2022/11/13 |
| Horn Antenna ETS-Lindgren | 3117-PA | 00215857 | 2021/11/14 | 2022/11/13 |
| Horn Antenna Schwarzbeck | BBHA 9170 | 212 | 2021/10/13 | 2022/10/12 |
| Notch Filter MICRO-TRONICS | BRC50703-01 | 010 | 2022/5/26 | 2023/5/25 |
| Pre-amplifier HP | 8449B | 3008A01292 | 2022/2/17 | 2023/2/16 |
| Pre_Amplifier EMCI | EMC0126545 | 980076 | 2022/2/17 | 2023/2/16 |
| | EMC184045B | 980235 | 2022/2/17 | 2023/2/16 |
| RF Coaxial Cable EM | EM102-KMKM-3.5+1M | EM102-KMKM-3.5+1M-02 | 2022/7/7 | 2023/7/6 |
| Software BVADT | Radiated_V8.7.08 | N/A | N/A | N/A |
| Spectrum Keysight | N9020B | MY60110438 | 2021/12/8 | 2022/12/7 |
| | | MY60112260 | 2022/5/21 | 2023/5/20 |
| Spectrum Analyzer Agilent | E4446A | MY51100009 | 2022/6/27 | 2023/6/26 |
| Test Receiver Agilent | N9038A | MY51210137 | 2022/6/9 | 2023/6/8 |
| Turn Table & Tower Max Full | MF7802 | MF780208216 | N/A | N/A |


Notes:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in Linkou 966 Chamber 3 (CH 10).
3. Tested Date: 2022/8/13

7.3 Test Arrangement

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at an accredited chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The height of antenna can be varied from one meter to four meters, the height of adjustment depends on the EUT height and the antenna 3dB beamwidth both, to detect the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The spectrum analyzer system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz.

Note: The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection (PK) at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz for Average detection (AV) at frequency above 1GHz.



* :depends on the EUT height and the antenna 3dB beamwidth both.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

7.4 Test Results

Mode A


| | | | |
|------------------------|----------------|---|--------------------------------|
| Frequency Range | 1GHz ~ 6GHz | Detector Function & Resolution Bandwidth | Peak (PK) / Average (AV), 1MHz |
| Input Power | 230 Vac, 50 Hz | Environmental Conditions | 25°C, 71% RH |
| Tested By | Adam Chen | | |

Antenna Polarity & Test Distance : Horizontal at 3 m

| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
|-----------|-----------------|-------------------------|----------------|--------------|--------------------|----------------------|------------------|--------------------------|
| 1 | 1325.07 | 55.13 PK | 76.00 | -20.87 | 1.05 H | 158 | 58.95 | -3.82 |
| 2 | 1325.07 | 47.69 AV | 56.00 | -8.31 | 1.05 H | 158 | 51.51 | -3.82 |
| 3 | 2132.29 | 51.06 PK | 76.00 | -24.94 | 1.00 H | 198 | 51.85 | -0.79 |
| 4 | 2132.29 | 36.98 AV | 56.00 | -19.02 | 1.00 H | 198 | 37.77 | -0.79 |
| 5 | 2399.86 | 54.23 PK | 76.00 | -21.77 | 1.29 H | 205 | 54.15 | 0.08 |
| 6 | 2399.86 | 37.25 AV | 56.00 | -18.75 | 1.29 H | 205 | 37.17 | 0.08 |
| 7 | 2979.62 | 51.43 PK | 76.00 | -24.57 | 1.54 H | 111 | 49.38 | 2.05 |
| 8 | 2979.62 | 37.89 AV | 56.00 | -18.11 | 1.54 H | 111 | 35.84 | 2.05 |
| 9 | 3721.31 | 55.69 PK | 80.00 | -24.31 | 1.00 H | 1 | 50.63 | 5.06 |
| 10 | 3721.31 | 42.01 AV | 60.00 | -17.99 | 1.00 H | 1 | 36.95 | 5.06 |
| 11 | 5400.03 | 60.31 PK | 80.00 | -19.69 | 2.37 H | 106 | 52.52 | 7.79 |
| 12 | 5400.03 | 53.12 AV | 60.00 | -6.88 | 2.37 H | 106 | 45.33 | 7.79 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
– Pre-Amplifier Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value




| | | | |
|------------------------|----------------|---|--------------------------------|
| Frequency Range | 1GHz ~ 6GHz | Detector Function & Resolution Bandwidth | Peak (PK) / Average (AV), 1MHz |
| Input Power | 230 Vac, 50 Hz | Environmental Conditions | 25°C, 71% RH |
| Tested By | Adam Chen | | |

| Antenna Polarity & Test Distance : Vertical at 3 m | | | | | | | | |
|--|-----------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| No | Frequency (MHz) | Emission Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Antenna Height (m) | Table Angle (Degree) | Raw Value (dBuV) | Correction Factor (dB/m) |
| 1 | 1324.98 | 60.12 PK | 76.00 | -15.88 | 2.58 V | 359 | 63.95 | -3.83 |
| 2 | 1324.98 | 47.98 AV | 56.00 | -8.02 | 2.58 V | 359 | 51.81 | -3.83 |
| 3 | 1844.24 | 50.63 PK | 76.00 | -25.37 | 2.34 V | 10 | 52.40 | -1.77 |
| 4 | 1844.24 | 35.86 AV | 56.00 | -20.14 | 2.34 V | 10 | 37.63 | -1.77 |
| 5 | 2400.07 | 55.68 PK | 76.00 | -20.32 | 1.29 V | 204 | 55.60 | 0.08 |
| 6 | 2400.07 | 37.31 AV | 56.00 | -18.69 | 1.29 V | 204 | 37.23 | 0.08 |
| 7 | 2981.33 | 55.76 PK | 76.00 | -20.24 | 1.12 V | 354 | 53.70 | 2.06 |
| 8 | 2981.33 | 47.43 AV | 56.00 | -8.57 | 1.12 V | 354 | 45.37 | 2.06 |
| 9 | 4000.04 | 55.63 PK | 80.00 | -24.37 | 1.61 V | 153 | 50.31 | 5.32 |
| 10 | 4000.04 | 39.89 AV | 60.00 | -20.11 | 1.61 V | 153 | 34.57 | 5.32 |
| 11 | 5399.85 | 59.04 PK | 80.00 | -20.96 | 2.62 V | 113 | 51.25 | 7.79 |
| 12 | 5399.85 | 52.13 AV | 60.00 | -7.87 | 2.62 V | 113 | 44.34 | 7.79 |

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Pre-Amplifier Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value



8 Harmonics Current Measurement

8.1 Limits

| Limits for Class A equipment | | Limits for Class D equipment | | |
|------------------------------|--------------------------------------|------------------------------|--|--------------------------------------|
| Harmonic Order n | Max. permissible harmonics current A | Harmonic Order n | Max. permissible harmonics current per watt mA/W | Max. permissible harmonics current A |
| Odd harmonics | | Odd Harmonics only | | |
| 3 | 2.30 | 3 | 3.4 | 2.30 |
| 5 | 1.14 | 5 | 1.9 | 1.14 |
| 7 | 0.77 | 7 | 1.0 | 0.77 |
| 9 | 0.40 | 9 | 0.5 | 0.40 |
| 11 | 0.33 | 11 | 0.35 | 0.33 |
| 13 | 0.21 | 13 | 0.30 | 0.21 |
| $15 \leq n \leq 39$ | $0.15 \times 15/n$ | $15 \leq n \leq 39$ | $3.85/n$ | $0.15 \times 15/n$ |
| Even harmonics | | | | |
| 2 | 1.08 | | | |
| 4 | 0.43 | | | |
| 6 | 0.30 | | | |
| $8 \leq n \leq 40$ | $0.23 \times 8/n$ | | | |

Notes: 1. Class A and Class D are classified according to section 5 of EN 61000-3-2.

2. According to section 7 of EN 61000-3-2, the above limits for all equipment except for lighting equipment having an active input power > 75 W and no limits apply for equipment with an active input power up to and including 75 W.

8.2 Classification of Equipment

| Class A | Class B | Class C | Class D |
|--|--|---------------------|---|
| Balanced three-phase equipment; Household appliances excluding equipment as Class D; Tools excluding portable tools; Dimmers for incandescent lamps; Audio equipment; Equipment not specified in one of the three other classes. | Portable tools; Arc welding equipment which is not professional equipment. | Lighting equipment. | Equipment having a specified power less than or equal to 600 W of the following types: Personal computers and personal computer monitors; Television receivers; Refrigerators and freezers having one or more variable-speed drives to control compressor motor(s). |

8.3 Test Instruments


| Description Manufacturer | Model No. | Serial No. | Calibrated Date | Calibrated Until |
|---|---------------|-----------------------|-----------------|------------------|
| Harmonics and Flicker Analyzer TESEQ | PROFLINE 2105 | 1632A00983&1639A01863 | 2022/6/8 | 2023/6/7 |
| Software | CTS 4 | N/A | N/A | N/A |

Notes:

- The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
- The test was performed in Linkou EMS Room No.1.
- Tested Date: 2022/8/25

8.4 Test Arrangement

- a. The EUT was placed on the top of a wooden table 0.8 meters above the ground and operated to produce the maximum harmonic components under normal operating conditions for each successive harmonic component in turn.
- b. The correspondent test program of test instrument to measure the current harmonics emanated from EUT is chosen. The measure time shall be not less than the time necessary for the EUT to be exercised.



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

8.5 Test Results

Mode A

| | | | |
|--------------------------|----------|-------------------------------------|--------------------------|
| Test Duration | 5 min | Fundamental Voltage / Ampere | 230.65 Vrms / 0.656 Arms |
| Power Consumption | 130.3 W | Power Frequency | 50 Hz |
| Power Factor | 0.887 | Environmental Conditions | 24°C, 75% RH |
| Tested By | Joey Liu | | |

| Harm# | Harms (avg) (A) | 100% Limit (A) | Harms (max) (A) | 150% Limit (A) |
|-------|-----------------|----------------|-----------------|----------------|
| 1 | 0.586 | - | 1.643 | - |
| 3 | 0.167 | 0.443 | 0.179 | 0.665 |
| 5 | 0.050 | 0.248 | 0.054 | 0.371 |
| 7 | 0.028 | 0.130 | 0.035 | 0.195 |
| 9 | 0.018 | 0.065 | 0.024 | 0.098 |
| 11 | 0.015 | 0.046 | 0.020 | 0.068 |
| 13 | 0.013 | 0.039 | 0.017 | 0.059 |
| 15 | 0.018 | 0.034 | 0.024 | 0.051 |
| 17 | 0.023 | 0.030 | 0.027 | 0.045 |
| 19 | 0.002 | 0.026 | 0.004 | 0.040 |
| 21 | 0.008 | 0.024 | 0.010 | 0.036 |
| 23 | 0.007 | 0.022 | 0.008 | 0.033 |
| 25 | 0.007 | 0.020 | 0.009 | 0.030 |
| 27 | 0.012 | 0.019 | 0.014 | 0.028 |
| 29 | 0.004 | 0.017 | 0.005 | 0.026 |
| 31 | 0.009 | 0.016 | 0.010 | 0.024 |
| 33 | 0.005 | 0.015 | 0.008 | 0.023 |
| 35 | 0.007 | 0.014 | 0.010 | 0.021 |
| 37 | 0.002 | 0.014 | 0.003 | 0.020 |
| 39 | 0.005 | 0.013 | 0.006 | 0.019 |

Note: Dynamic limits were applied for this test. The highest harmonics values in the above table may not occur at the same window as the maximum harmonics/limit ratio.

9 Voltage Fluctuations and Flicker Measurement

9.1 Limits

| Test item | Limit | Note |
|----------------|-------|---|
| P_{st} | 1.0 | P_{st} : short-term flicker severity. |
| P_{lt} | 0.65 | P_{lt} : long-term flicker severity. |
| T_{max} (ms) | 500 | T_{max} : maximum time duration during the observation period that the voltage deviation $d(t)$ exceeds the limit for d_c . |
| d_{max} (%) | 4 | d_{max} : maximum absolute voltage change during an observation period. |
| d_c (%) | 3.3 | d_c : maximum steady state voltage change during an observation period. |

9.2 Test Instruments


| Description Manufacturer | Model No. | Serial No. | Calibrated Date | Calibrated Until |
|--|---------------|-----------------------|--------------------|---------------------|
| Harmonics and Flicker Analyzer TESEQ | PROFLINE 2105 | 1632A00983&1639A01863 | 2022/6/8 | 2023/6/7 |
| Software | CTS 4 | N/A | N/A | N/A |

Notes:

- The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
- The test was performed in Linkou EMS Room No.1.
- Tested Date: 2022/8/25

9.3 Test Arrangement

- The EUT was placed on the top of a wooden table 0.8 meters above the ground and operated to produce the most unfavorable sequence of voltage changes under normal operating conditions.
- During the flick measurement, the measure time shall include that part of whole operation cycle in which the EUT produce the most unfavorable sequence of voltage changes. The observation period for short-term flicker indicator is 10 minutes and the observation period for long-term flicker indicator is 2 hours.



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

9.4 Test Results

Mode A

| | | | |
|-------------------------|----------------|---------------------------------|--------------|
| Observation (Tp) | 10 min | | |
| Input Power | 230 Vac, 50 Hz | Environmental Conditions | 24°C, 75% RH |
| Tested By | Joey Liu | | |

| Test Parameter | Measurement Value | Limit | Remarks |
|----------------|-------------------|-------|---------|
| P_{st} | 0.356 | 1.00 | Pass |
| P_{lt} | 0.155 | 0.65 | Pass |
| T_{max} (ms) | 0.000 | 500 | Pass |
| d_{max} (%) | 0.000 | 4.00 | Pass |
| d_c (%) | 0.000 | 3.30 | Pass |

Notes:

- P_{st} means short-term flicker indicator.
- P_{lt} means long-term flicker indicator.
- T_{max} means accumulated time value of $d(t)$ with a deviation exceeding 3.3 %.
- d_{max} means maximum relative voltage change.
- d_c means maximum relative steady-state voltage change.

10 Electrostatic Discharge Immunity Test (ESD)

10.1 Test Specification

| | |
|-----------------------------|--|
| Basic Standard: | EN 61000-4-2 |
| Discharge Impedance: | 330 ohm / 150 pF |
| Discharge Voltage: | Air Discharge: ± 2 , ± 4 , ± 8 kV (Direct) Contact Discharge: ± 2 , ± 4 , ± 6 kV (Indirect & Direct) |
| Number of Discharge: | Minimum 20 times at each test point |
| Discharge Mode: | Single Discharge |
| Discharge Period: | 1-second minimum |

10.2 Test Instruments

| Description Manufacturer | Model No. | Serial No. | Calibrated Date | Calibrated Until |
|-----------------------------|-----------------------------------|-------------------------|--------------------|---------------------|
| ESD Generator EM Test | Dito//DM-150/330//DM-150/330-rfci | P1315117252/P1317117852 | 2022/7/7 | 2023/7/6 |

Notes:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in Linkou ESD Room No.03.
3. Tested Date: 2022/8/27

10.3 Test Arrangement

- Electrostatic discharges were applied only to those points and surfaces of the EUT that are accessible to users during normal operation.
- The test was performed with at least ten single discharges on the pre-selected points in the most sensitive polarity.
- The time interval between two successive single discharges was at least 1 second.
- The ESD generator was held perpendicularly to the surface to which the discharge was applied and the return cable was at least 0.2 meters from the EUT.
- Contact discharges were applied to the non-insulating coating, with the pointed tip of the generator penetrating the coating and contacting the conducting substrate.
- Air discharges were applied with the round discharge tip of the discharge electrode approaching the EUT as fast as possible (without causing mechanical damage) to touch the EUT. After each discharge, the ESD generator was removed from the EUT and re-triggered for a new single discharge. The test was repeated until all discharges were complete.
- At least ten single discharges (in the most sensitive polarity) were applied to the **Horizontal Coupling Plane** at points on each side of the EUT. The ESD generator was positioned at a distance of 0.1 meters from the EUT with the discharge electrode touching the **HCP**.
- At least ten single discharges (in the most sensitive polarity) were applied to the center of one vertical edge of the **Vertical Coupling Plane** in sufficiently different positions that the four faces of the EUT were completely illuminated. The **VCP** (dimensions 0.5m x 0.5m) was placed vertically to and 0.1 meters from the EUT.




TABLE-TOP EQUIPMENT

The configuration consisted of a wooden table 0.8 meters high standing on the **Ground Reference Plane**. The **GRP** consisted of a sheet of aluminum at least 0.25mm thick, and 2.5 meters square connected to the protective grounding system. A **Horizontal Coupling Plane** (1.6m x 0.8m) was placed on the table and attached to the **GRP** by means of a cable with 940kΩ total impedance. The equipment under test, was installed in a representative system as described in section 7 of EN 61000-4-2, and its cables were placed on the **HCP** and isolated by an insulating support of 0.5mm thickness. A distance of 1-meter minimum was provided between the EUT and the walls of the laboratory and any other metallic structure.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

10.4 Test Results

Mode A

| | | | |
|--------------------------|-------------------------|-----------|----------|
| Input Power | 230Vac, 50 Hz | Tested by | Joey Liu |
| Environmental Conditions | 24°C, 44% RH, 1000 mbar | | |

Test Results of Direct Application

| Discharge Level (kV) | Polarity (+/-) | Test Point | Contact Discharge | Air Discharge | Performance Criterion |
|----------------------|----------------|------------------|-------------------|---------------|-----------------------|
| 2 | +/- | 1~6,20~26,36~40 | Note 1 | --- | A |
| 4, 6 | +/- | 1~6,20~26,36~40 | Note 2 | --- | B |
| 2, 4 | +/- | 7~19,27~35,41,42 | --- | Note 1 | A |
| 8 | +/- | 7~8,35,41,42 | --- | Note 1 | A |
| 8 | +/- | 9~19,27~34 | --- | Note 2 | B |

Description of test points of direct application: Please refer to following page for representative mark only.

Test Results of Indirect Application



| Discharge Level (kV) | Polarity (+/-) | Test Point | Horizontal Coupling Plane | Vertical Coupling Plane | Performance Criterion |
|----------------------|----------------|------------|---------------------------|-------------------------|-----------------------|
| 2, 4, 6 | +/- | Four Side | Note 1 | Note 1 | A |



Description of test points of indirect application:

1. Front side
2. Rear side
3. Right side
4. Left side

Note: 1. The EUT is operated normal during the test.
 2. There are flicker on the Display screen, but auto recover after test

Description of Test Points





11 Radio-frequency Electromagnetic Field Immunity Test (RS)

11.1 Test Specification

| | |
|----------------------------------|------------------------------------|
| Basic Standard: | EN 61000-4-3 |
| Frequency Range, Field Strength: | 80-800 MHz, 20V/m ¹ |
| | 800-1000 MHz, 20V/m |
| | 1400-2000 MHz, 10V/m |
| | 2000-2700 MHz, 5V/m |
| | 5100-6000 MHz, 3V/m |
| Modulation: | 1kHz Sine Wave, 80%, AM Modulation |
| Frequency Step: | 1 % of preceding frequency value |
| Polarity of Antenna: | Horizontal and Vertical |
| Antenna Height: | 1.5m |
| Dwell Time: | 3 seconds |

Note 1: This limit applies to equipment mounted in the passenger compartments, drivers cab or external to the rolling stock (roof, underframe). For equipment mounted in all other areas a severity level of 10 V/m may be used.

11.2 Test Instruments

| Description Manufacturer | Model No. | Serial No. | Calibrated Date | Calibrated Until |
|---|-----------------------|------------|-----------------|------------------|
| Amplifier BONN | BSA 0125-800 | 1912556 | N/A | N/A |
| Amplifier TESTQ | CBA 1G-275 | T44344 | N/A | N/A |
| Audio analyzer R&S | UPV | 104565 | 2022/5/10 | 2023/5/9 |
| Band pass filter B&K | WH3278 | N/A | 2021/11/17 | 2022/11/16 |
| BiconiLog Antenna EMCO | 3141 | 1001 | N/A | N/A |
| CHANCE MOST Full Anechoic Chamber (9x5x3m) | Chance Most | RS-002 | 2022/2/3 | 2023/2/2 |
| Controller AR | SC1000M3 | 305910 | N/A | N/A |
| Ear Simulator Telephonometry B&K | 4185 | 2553594 | N/A | N/A |
| High Gain Horn Antenna AR | AT4010 | 0329800 | N/A | N/A |
| LOG ANTENNA Schwarzbeck | Schwarzbeck Stlp 9149 | 9149-260 | N/A | N/A |
| Log-Periodic Antenna AR | AT6080 | 0329465 | N/A | N/A |
| Power Amplifier AR | 35S4G8AM4 | 0326094 | N/A | N/A |
| | 100S1G4M3 | 0329249 | N/A | N/A |
| Power Meter BOONTON | 4232A | 94901 | 2022/6/6 | 2023/6/5 |
| Power Sensor BOONTON | 51011-EMC | 32807 | 2022/6/6 | 2023/6/5 |
| | | 32832 | 2022/6/6 | 2023/6/5 |
| Pressure-field Microphone B&K | 4192 | 3190854 | 2021/12/20 | 2022/12/19 |
| Signal Generator Agilent | E8257D | MY48050465 | 2022/6/29 | 2023/6/28 |
| Software BVADT | RS_V7.6 | N/A | N/A | N/A |
| Software | ABMS_V7.4.3 | N/A | N/A | N/A |
| Two channel microphone conditioning amplifier B&K | 2690 OS2 | 3001996 | 2021/11/17 | 2022/11/16 |
| Wireless Connection Tester R&S | CMW270 | 101075 | 2022/4/18 | 2023/4/17 |

Notes:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in Linkou RS Room No.02.
3. Tested Date: 2022/8/24

11.3 Test Arrangement

The test procedure was in accordance with EN 61000-4-3.

- The testing was performed in a fully anechoic chamber.
- The frequency ranges and field strength levels are 80-800 MHz, 20V/m, 800-1000 MHz, 20V/m, 1400-2000 MHz, 10V/m, 2000-2700 MHz, 5V/m and 5100-6000 MHz, 3V/m with the signal 80% amplitude modulated with a 1kHz sine wave.
- The test was performed with the EUT exposed to both vertically and horizontally polarized fields on each of the four sides.




Table-top Equipment

The EUT installed in a representative system as described in section 7 of EN 61000-4-3 was placed on a non-conductive table 0.8 meters in height. The system under test was connected to the power and signal wire according to relevant installation instructions.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

11.4 Test Results

Mode A

| | | | |
|--------------------------|---------------|-----------|----------|
| Input Power | 230Vac, 50 Hz | Tested by | Joey Liu |
| Environmental Conditions | 24°C, 76% RH | | |

| Frequency (MHz) | Polarity | Azimuth(°) | Applied Field Strength | | Observation | Performance Criterion |
|-----------------|----------|-----------------|------------------------|---------------|-------------|-----------------------|
| | | | (V/m) | Modulation | | |
| 80 - 800 | V&H | 0, 90, 180, 270 | 20 | 80% AM (1kHz) | Note | A |
| 800 - 1000 | V&H | 0, 90, 180, 270 | 20 | 80% AM (1kHz) | Note | A |
| 1400 - 2000 | V&H | 0, 90, 180, 270 | 10 | 80% AM (1kHz) | Note | A |
| 2000 - 2700 | V&H | 0, 90, 180, 270 | 5 | 80% AM (1kHz) | Note | A |
| 5100 - 6000 | V&H | 0, 90, 180, 270 | 3 | 80% AM (1kHz) | Note | A |

Note: The EUT is operated normal during the test.

12 Electrical Fast Transient/Burst Immunity Test (EFT)

12.1 Test Specification

| | |
|-------------------------------|---|
| Basic Standard: | EN 61000-4-4 |
| Test Voltage: | Signal & communication, process measurement & control ports: $\pm 2\text{kV}$, Capacitive clamp Battery referenced ports (except at the output of energy sources), Auxiliary a.c. power input ports (rated voltage $\leq 400\text{ Vrms}$): $\pm 2\text{kV}$ |
| Impulse Repetition Frequency: | 5kHz |
| Impulse Wave Shape: | 5/50 (T_r/T_h) ns |
| Burst Duration: | 15 ms |
| Burst Period: | 300 ms |
| Test Duration: | 1 min. |

12.2 Test Instruments


| Description Manufacturer | Model No. | Serial No. | Calibrated Date | Calibrated Until |
|-----------------------------|-----------|------------|--------------------|---------------------|
| Burst generator Haefely | PEFT 4010 | 154954 | 2022/3/29 | 2023/3/28 |

Notes:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in Linkou EFT Room.
3. Tested Date: 2022/8/26

12.3 Test Arrangement

- Both positive and negative polarity discharges were applied.
- The distance between any coupling devices and the EUT should be 0.5 m for table-top equipment testing, and 1.0 m for floor standing equipment.
- The duration time of each test sequential was 1 minute.
- The transient/burst waveform was in accordance with EN 61000-4-4, 5/50 ns.



NOTE:

- location for supply line coupling
- location for signal lines coupling

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

12.4 Test Results

Mode A

| | | | |
|--------------------------|---------------|-----------|----------|
| Input Power | 230Vac, 50 Hz | Tested by | Joey Liu |
| Environmental Conditions | 23°C, 72% RH | | |

Battery referenced ports (except at the output of energy sources),
 Auxiliary a.c. power input ports (rated voltage \leq 400 Vrms)

| Voltage (kV) | Test Point | Polarity (+/-) | Observation | Performance Criterion |
|--------------|------------|----------------|-------------|-----------------------|
| 2 | L | +/- | Note | A |
| 2 | N | +/- | Note | A |
| 2 | PE | +/- | Note | A |
| 2 | L-N-PE | +/- | Note | A |

Signal & communication, process measurement & control ports

| Voltage (kV) | Test Point | Polarity (+/-) | Observation | Performance Criterion |
|--------------|-----------------|----------------|-------------|-----------------------|
| 2 | LAN 1 | +/- | Note | A |
| 2 | LAN 2 | +/- | Note | A |
| 2 | LAN CARD Port 1 | +/- | Note | A |
| 2 | LAN CARD Port 4 | +/- | Note | A |

Note: The EUT is operated normal during the test.

13 Surge Immunity Test

13.1 Test Specification

| | |
|--------------------------|--|
| Basic Standard: | EN 61000-4-5 |
| Wave-Shape: | Battery referenced ports (except at the output of energy sources), Auxiliary a.c. power input ports (rated voltage ≤ 400 Vrms): 1.2/50 μ s Open Circuit Voltage 8/20 μ s Short Circuit Current |
| Test Voltage: | Line to line: ± 0.5 kV, ± 1 kV, Line to ground: ± 0.5 kV, ± 1 kV, ± 2 kV output impedance of 42 Ω (40 Ω and 2 Ω generator) and a coupling capacitance of 0,5 μ F |
| AC Phase Angle (degree): | 0°, 90°, 180°, 270° |
| Pulse Repetition Rate: | 1 time / 20 sec. |
| Number of Tests: | 5 positive and 5 negative at selected points |

13.2 Test Instruments

| Description Manufacturer | Model No. | Serial No. | Calibrated Date | Calibrated Until |
|---|------------|------------|-----------------|------------------|
| CDN for Unshielded Unsymmetrical Signal & Data Lines TESEQ | CDN117 | 40144 | 2022/8/23 | 2023/8/22 |
| Coupling Decoupling Network EMC-Partner | CDN-UTP8 | 045 | 2022/8/2 | 2023/8/1 |
| Coupling Decoupling Network TESEQ | CDN HSS-2 | 41009 | 2022/4/18 | 2023/4/17 |
| Surge Coupling Decoupling Network TESEQ | CDN 118-T8 | 40386 | 2021/8/30 | 2022/8/29 |
| Surge&EFT Generators TESEQ | NSG 3060 | 1572 | 2022/4/18 | 2023/4/17 |


Notes:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in Linkou EMS Room No.02.
3. Tested Date: 2022/8/25

13.3 Test Arrangement

The surge is to be applied to the EUT power supply terminals via the capacitive coupling network. Decoupling networks are required in order to avoid possible adverse effects on equipment not under test that may be powered by the same lines, and to provide sufficient decoupling impedance to the surge wave. The power cord between the EUT and the coupling/decoupling networks shall be 2 meters in length (or shorter).

For double-insulated products without PE or external earth connections, the test shall be done in a similar way as for grounded products but without adding any additional external grounded connections. If there are no other possible connections to earth, line-to-ground tests may be omitted.



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

13.4 Test Results

Mode A

| | | | |
|--------------------------|---------------|-----------|----------|
| Input Power | 230Vac, 50 Hz | Tested by | Joey Liu |
| Environmental Conditions | 24°C, 73% RH | | |

Battery referenced ports (except at the output of energy sources),
 Auxiliary a.c. power input ports (rated voltage ≤ 400 Vrms)

| Voltage (kV) | Test Point | Polarity (+/-) | Observation | Performance Criterion |
|--------------|------------|----------------|-------------|-----------------------|
| 0.5, 1 | L-N | +/- | Note | A |
| 0.5, 1, 2 | L-PE | +/- | Note | A |
| 0.5, 1, 2 | N-PE | +/- | Note | A |

Note: The EUT is operated normal during the test.

14 Immunity to Conducted Disturbances Induced by RF Fields (CS)

14.1 Test Specification

| | |
|------------------|--|
| Basic Standard: | EN 61000-4-6 |
| Frequency Range: | 0.15 MHz - 80 MHz |
| Voltage Level: | Battery referenced ports (except at the output of energy sources), Auxiliary a.c. power input ports (rated voltage \leq 400 Vrms), Signal & communication, process measurement & control ports: 10 V |
| Modulation: | 1kHz Sine Wave, 80%, AM Modulation |
| Frequency Step: | 1 % of preceding frequency value |
| Dwell Time | 3 seconds |

14.2 Test Instruments

| Description Manufacturer | Model No. | Serial No. | Calibrated Date | Calibrated Until |
|---------------------------------------|----------------|------------|--------------------|---------------------|
| Amplifier AR | 75A250AM1 | 306331 | N/A | N/A |
| Audio analyzer R&S | UPV | 104565 | 2022/5/10 | 2023/5/9 |
| CDN FCC | FCC-801-M5-50A | 100018 | 2022/1/18 | 2023/1/17 |
| CDN TESEQ | CDN S200 | 53490 | 2022/2/24 | 2023/2/23 |
| | CDN S400 | 52115 | 2022/2/24 | 2023/2/23 |
| CDN Calibration Kit TESEQ | CDN T8S | 29459 | 2022/2/22 | 2023/2/21 |
| CDN M2-16Amp FCC | FCC-801-M2-16A | 01047 | 2022/2/23 | 2023/2/22 |
| Coupling Decoupling Network TESEQ | CDN M432S | 56519 | 2022/2/23 | 2023/2/22 |
| | CDN S751A | 56435 | 2022/2/21 | 2023/2/20 |
| | | 56436 | 2022/2/22 | 2023/2/21 |
| | CDN ST08A | 56525 | 2022/2/21 | 2023/2/20 |
| | | 56527 | 2022/2/21 | 2023/2/20 |
| | CDN T2A-10 | 54942 | 2022/2/22 | 2023/2/21 |
| | CDN T8-10 | 40376 | 2022/2/22 | 2023/2/21 |
| | CDN T8-230 | 56641 | 2022/2/22 | 2023/2/21 |
| | | 56642 | 2022/2/22 | 2023/2/21 |
| | | 56643 | 2022/2/22 | 2023/2/21 |
| CDN T800 | 34428 | 2022/2/22 | 2023/2/21 | |
| CDN T400A | 49918 | 2022/2/23 | 2023/2/22 | |
| Coupling/Dcoupling Network EM TEST | CDN M1/32A | 306508 | 2022/2/23 | 2023/2/22 |
| Coupling/Dcoupling Network TESEQ | CDN M232 | 37702 | 2022/2/23 | 2023/2/22 |
| | CDN M332 | 41256 | 2022/2/23 | 2023/2/22 |
| | | 41258 | 2022/2/23 | 2023/2/22 |
| Current Clamp FCC | F-120-9A | 361 | 2022/8/17 | 2023/8/16 |


| Description Manufacturer | Model No. | Serial No. | Calibrated Date | Calibrated Until |
|---|--------------|------------|--------------------|---------------------|
| Digital Sweep Function Generator Topward | 8120 | 984801 | N/A | N/A |
| Ear Simulator Telephonometry B&K | 4185 | 2553594 | N/A | N/A |
| FCC EM Injection Clamp FCC | F-203I-23mm | 455 | N/A | N/A |
| Mouth Simulator B&K | 4227 | 2630632 | N/A | N/A |
| POWER AMPLIFIER B&K | 2716C | 2610979 | N/A | N/A |
| Power Meter R & S | NRVD | 837794/040 | 2021/10/19 | 2022/10/18 |
| Power Sensor R & S | NRV-Z5 | 837878/039 | 2021/10/19 | 2022/10/18 |
| Pressure-field Microphone B&K | 4192 | 2735407 | 2021/11/19 | 2022/11/18 |
| R&S SML03 S.G R&S | SML03 | 101801 | 2022/1/11 | 2023/1/10 |
| Software BVADT | ABMS_ V7.4.3 | N/A | N/A | N/A |
| | CS_ V7.4.2 | N/A | N/A | N/A |
| Two channel microphone conditioning amplifier B&K | 2690 OS2 | 3001996 | 2021/11/17 | 2022/11/16 |
| Wireless Connection Tester R&S | CMW270 | 101075 | 2022/4/18 | 2023/4/17 |

Notes:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in Linkou CS Room No.1.
3. Tested Date: 2022/8/22

14.3 Test Arrangement

- The EUT shall be tested within its intended operating and climatic conditions.
- An artificial hand was placed on the hand-held accessory and connected to the ground reference plane.
- One of the CDNs not used for injection was terminated with 50 ohm, providing only one return path. All other CDNs were coupled as decoupling networks.
- The frequency range is swept from 150 kHz to 80 MHz, using the signal level established during the setting process and with a disturbance signal of 80 % amplitude. The signal is modulated with a 1 kHz sine wave, pausing to adjust the RF signal level or the switch coupling devices as necessary. Where the frequency is swept incrementally, the step size shall not exceed 1 % of the preceding frequency value.
- Attempts should be made to fully exercise the EUT during testing, and to fully interrogate all exercise modes selected for susceptibility.



IEC 2606/13

- Note:**
- The EUT clearance from any metallic obstacles shall be at least 0,5 m.
 - Interconnecting cables (≤ 1 m) belonging to the EUT shall remain on the insulating support.
 - The equipment to be tested is placed on an insulating support of 0.1 meters height above a ground reference plane. All relevant cables shall be provided with the appropriate coupling and decoupling devices at a distance between 0.1 meters and 0.3 meters from the projected geometry of the EUT on the ground reference plane.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

14.4 Test Results

Mode A


| | | | |
|--------------------------|---------------|-----------|----------|
| Input Power | 230Vac, 50 Hz | Tested by | Joey Liu |
| Environmental Conditions | 23°C, 69% RH | | |

| Frequency (MHz) | Level (V rms) | Tested Line | Injection Method | Return Path | Observation | Remark | Performance Criterion |
|-----------------|---------------|----------------|------------------|-------------|-------------|--------|-----------------------|
| 0.15 – 80 | 10 | AC Power | CDN-M3 | CDN-ST08A | Note | - | A |
| 0.15 – 80 | 10 | LAN 1 (1G) | CDN-ST08A | CDN-M3 | Note | - | A |
| 0.15 – 80 | 10 | LAN 2 (2.5G) | CDN-ST08A | CDN-M3 | Note | - | A |
| 0.15 – 80 | 10 | LAN Card Port1 | CDN-ST08A | CDN-M3 | Note | - | A |
| 0.15 – 80 | 10 | LAN Card Port4 | CDN-ST08A | CDN-M3 | Note | - | A |


Note: The EUT is operated normal during the test.

15 Pictures of Test Arrangements


15.1 Conducted Disturbance at Auxiliary a.c. or d.c. power ports




15.2 Radiated Disturbance up to 1 GHz



15.3 Radiated Disturbance above 1 GHz




15.4 Harmonics Current, Voltage Fluctuations and Flicker Measurement



15.5 Electrostatic Discharge Immunity Test (ESD)




15.6 Radio-frequency Electromagnetic Field Immunity Test (RS)




15.7 Fast Transients (EFT)

Mains port



LAN1



LAN2



LAN Card




15.8 Surge

Mains ports




15.9 Radio-frequency common mode (CS)


Mains port




LAN1



LAN2



LAN Card



Appendix – Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---